

ВИНТОВОЙ КОМПРЕССОР РАБОЧЕЙ ЧАСТОТЫ

+



Технические параметры винтового компрессора рабочей частоты

МОДЕЛЬ		BG10A	BG15A	BG20A	BG25A	BG30A	BG40A	BG50A
ОБЪЕМ РАСХОДА/ДАВЛЕНИЕ (М³/МИН)/МПА		1.2/0.7	1.7/0.7	2.4/0.7	2.9/0.7	3.5/0.7	4.7/0.7	6.4/0.7
		1.1/0.8	1.6/0.8	2.2/0.8	2.8/0.8	3.4/0.8	4.6/0.8	6.3/0.8
		0.9/1.0	1.3/1.0	2.0/1.0	2.7/1.0	3.2/1.0	—	—
		0.7/1.3	1.0/1.3	1.6/1.3	2.2/1.3	2.4/1.3	3.1/1.3	4.7/1.3
МОЩНОСТЬ (КВТ)		7.5	11	15	18.5	22	30	37
РАЗМЕР ТРУБОПРОВОДА		G1/2	G3/4	G3/4	G1	G1	G1	G1 1/2
ВЕС (КГ)		190	320	340	400	430	460	650
РАЗМЕР (ММ)	L(мм)	900	1150	1150	1350	1350	1350	1500
	W(мм)	650	750	750	850	850	850	1000
	H(мм)	860	960	960	1110	1110	1110	1350

МОДЕЛЬ		BG60A	BG75A	BG100A	BG125A	BG150A	BG180A	BG220A
ОБЪЕМ РАСХОДА/ДАВЛЕНИЕ (М³/МИН)/МПА		7.3/0.7	9.4/0.7	12.4/0.7	15.4/0.7	20.1/0.7	23.0/0.7	28.5/0.7
		7.2/0.8	9.3/0.8	12.2/0.8	15.0/0.8	19.9/0.8	22.5/0.8	28.0/0.8
		6.2/1.0	7.1/1.0	—	12.1/1.0	14.8/1.0	19.7/1.0	22.5/1.0
		—	6.1/1.3	9.1/1.3	—	12.0/1.3	14.6/1.3	21.5/1.3
МОЩНОСТЬ (КВТ)		45	55	75	90	110	132	160
РАЗМЕР ТРУБОПРОВОДА		G1 1/2	G2 1/2	G2 1/2	G2 1/2	DN65	DN65	DN100
ВЕС (КГ)		700	1100	1200	1500	1800	1900	3000
РАЗМЕР (ММ)	L(мм)	1500	1700	1700	2100	2250	2250	2900
	W(мм)	1000	1210	1210	1400	1510	1510	1800
	H(мм)	1350	1550	1550	1650	1850	1850	2100

МОДЕЛЬ		BG250A	BG270A	BG300A	BG350A	BG380A	BG420A	BG480A
ОБЪЕМ РАСХОДА/ДАВЛЕНИЕ (М³/МИН)/МПА		30.5/0.7	—	42.0/0.7	44.0/0.7	—	—	62.0/0.7
		30.0/0.8	—	41.5/0.8	43.5/0.8	—	—	61.0/0.8
		27.0/1.0	29.2/1.0	—	41.2/1.0	43.0/1.0	—	—
		22.5/1.3	25.5/1.3	28.5/1.3	31.5/1.3	41.0/1.3	42.5/1.3	—
МОЩНОСТЬ (КВТ)		185	200	220	250	280	315	355
РАЗМЕР ТРУБОПРОВОДА		DN100	DN125	DN125	DN125	DN125	DN125	DN150
ВЕС (КГ)		3500	4800	5000	5900	6500	7000	8000
РАЗМЕР (ММ)	L(мм)	2900	3800	3800	3800	3800	3800	4300
	W(мм)	1800	2300	2300	2300	2300	2300	2300
	H(мм)	2100	2300	2300	2200	2200	2200	2430